Computer Networking from LANs to WANs Hardware Software and Security 1st Edition Mansfield Test Bank

Full Download: http://alibabadownload.com/product/computer-networking-from-lans-to-wans-hardware-software-and-security-1st

Chapter 2: Network Topology

TRUE/FALSE

1.	The ne entire	a found in a small laboratory, or it may represent an net.				
	ANS:	T	PTS:	1	REF:	22
2.	2. With certain types of network communications, it is possible that duplicate packets of data are generated if an acknowledgement is not received by the source computer.					
	ANS:	T	PTS:	1	REF:	23
3. In a fully connected network, the number of plus one.						ctions at each node equals the total number of nodes
	ANS:	F	PTS:	1	REF:	25
4.	Even if the encrypted traffic is intercepted, chances are very small that the contents can be decrypted a suitably strong encryption method and key are used.					
	ANS:	T	PTS:	1	REF:	31
5.	5. A network that can be partitioned is secure and reliable.				iable.	
	ANS:	F	PTS:	1	REF:	31
MUL	TIPLE	CHOICE				
1.	pair ca a. ph		cable l		crowav c.	provided through dedicated phone lines, twisted e RF, ATM, or other form of electronic connection. physical infrastructure virtual interconnection
	ANS:	A	PTS:	1	REF:	22
2.	t a. pe	a large amount between the ma ermanent circui rtual circuit	chines.	a must be sent t	c.	machines on a network, it is possible to set up a virtual interface physical interface
	ANS:	В	PTS:	1	REF:	23
3.		nitted between PV N		computers at e	ach end c. d.	sh private communication by encrypting the data of the connection. PVN VPN 23-24
4.	Seven a. 14	-	d nodes	require1		28

	b. 21			d.	35			
	ANS: B	PTS:	1	REF:	25			
5.	A network uses a. ring b. star	a singl	e shared comm	c.	munication media that all nodes tap into. bus string			
	ANS: C	PTS:	1	REF:	26			
6.	In a bus network, if t a. collision b. compression	wo or n	nore nodes trans	c.	ta at the same time, a occurs. collusion contention			
	ANS: A	PTS:	1	REF:	26			
7.	Token-ring networks a. media access uni b. multistation acce	ts		c.	rings, are connected using central station access units access units			
	ANS: B	PTS:	1	REF:	27			
8.	A(n) is a 32-bit a. MAC address b. TCP address	numbe	r used to locate	c.	entify nodes on the Internet. Ethernet address IP address			
	ANS: D	PTS:	1	REF:	29			
9.	A is a portion of a. subnet b. subunit	of a netv	vork.		slice subdivision			
	ANS: A	PTS:	1	REF:	29			
10.	exchange traffic. a. posting b. partner			c. d.	peering polling			
	ANS: C	PIS:	1	REF:	30			
COM	PLETION							
1.	A(n) circuit is a prearranged path through the network that all packets will travel for a particular session between machines.							
	ANS: virtual							
	PTS: 1	REF:	23					
2.	In a star network, all nodes connect to a central communications							
	ANS: hub							
	PTS: 1	REF:	25					

3.	is a logical, not physical, activity and is accomplished using a special subnet mask, such as 255.255.255.192.							
	ANS: Subnetting	5						
	PTS: 1	REF: 29						
4.		nd managed by a private organization or company than a public network.						
	ANS: private							
	PTS: 1	REF: 30						
5.	5. In terms of security and reliability, we must concern ourselves with what is required to our network.							
	ANS: partition							
	PTS: 1	REF: 31						
MAT	CHING							
	Match each item	with the correc	t statement below.					
	a. Tunnels			NAPs				
	b. Topology		e.	Cloud				
	c. Logical topol	ogy						
1.	Concerns the stru	cture of the cor	nnections between	the computers in a network				
	Concerns the structure of the connections between the computers in a network A graphical symbol used to describe a network without specifying the nature of the connections							
	Has to do with the path a packet of data takes through the network							
	Logical connections between the nodes of the VPN							
5.	Provide access to	Provide access to national and global network traffic						
1.	ANS: B	PTS: 1	REF:	22				
	ANS: E	PTS: 1	REF:					
	ANS: C	PTS: 1	REF:					
4.	ANS: A	PTS: 1	REF:	24				
5.	ANS: D	PTS: 1	REF:	29				

SHORT ANSWER

1. Describe a mesh network.

ANS:

In general, a mesh network is a collection of computers that are not connected in a bus, star, or ring topology. The term full mesh, or fully connected mesh, is only used when each node is connected to each other node. A partially connected network does not have as many links as a full mesh, making it less reliable.

PTS: 1 REF: 25

Computer Networking from LANs to WANs Hardware Software and Security 1st Edition Mansfield Test Bank

Full Download: http://alibabadownload.com/product/computer-networking-from-lans-to-wans-hardware-software-and-security-1st

2. Discuss the difference between a hub and a switch.

ANS:

One characteristic of a hub is that it broadcasts data received on one port to all other ports, essentially sending copies of data from one node to all other nodes on the LAN. In this way, each node on the network has an opportunity to see each packet of network data. A similar device called a switch learns where to send the data, eliminating a large majority of the broadcast traffic on the LAN. The switch also provides the Star topology.

PTS: 1 REF: 26

3. Describe a hybrid network.

ANS:

A hybrid network combines the components of two or more network topologies. Two star networks are connected (with three additional nodes) via a bus. This used to be a common way to implement Ethernet, with coax running between classrooms or laboratories and hubs in each room to form small subnetworks. Putting together a hybrid network takes careful planning, for there are various rules that dictate how the individual components may be connected and used. For example, when connecting Ethernet segments, a maximum of four repeaters may be used with five segments. Furthermore, if a 4-Mbps token-ring network is interfaced with a 10-Mbps Ethernet network, there are performance issues that must also be taken into consideration (because any Ethernet traffic is slowed down to 4Mbps on the token-ring side). In addition, the overall organization of the hybrid network, from a logical viewpoint, must be planned out as well.

PTS: 1 REF: 27

4. Discuss subnetting.

ANS:

Subnetting is a logical, not physical, activity and is accomplished using a special subnet mask, such as 255.255.255.192, that is logically ANDed with an IP address to determine its network address. The subnet mask is used to separate the IP address into two components: the network portion of the address and the host portion of the address. Here the host represents a node on the network. Nodes on different logical subnets cannot talk to each other without the use of a router, so using subnets allows the network designer to manage network traffic in a straightforward manner.

PTS: 1 REF: 29

5. Describe a private network.

ANS:

A private network is owned and managed by a private organization or company and may have a much larger bandwidth capability than a public network, depending on how much money its parent company invests in network infrastructure (by installing its own media between sites or by leasing private, dedicated communication lines from the telephone company). Private networks have higher maintenance costs per user and have the capability of restricting access to sensitive data.

PTS: 1 REF: 30-31