Engineering Mechanics Statics And Dynamics 13th Edition Hibbeler Solutions Manual

Full Download: https://testbanklive.com/download/engineering-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-and-dynamics-statics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-

		Tyr	hr
		I have inserted a note to remind that	Not an error, although it's a
		v_A could be greater than v_B	reasonable clarification. I'm not
		because the figure confuses, so they	sure how a single figure could
		could not to include absolute value to	show both possibilities. Leave the
12	Problem 12.26	the formula	main text alone.
			Error confirmed. The problem
			wording in the ISM also needs to
			be changed to match the text, and
			the EOB answer needs to be
		There is no solution for velocity	updated. See the insert material
12	Problem 12.154	at t=0.25s in ISM.	which follows after this errata list.
			Error confirmed. Change "from"
		The typo is in the textbook. There is	to "for" in reprint.
12	Problem 12.200	'from' instead of 'for'.	
- <u>-</u>	12.230		Error confirmed. The problem
			wording and art in the ISM also
		The textbook and the ISM are using	needs to be changed to match the
		different values of force, and we think	text, and the EOB answer needs to
		that ISM should be corrected to match	be updated. See the insert material
14	Problem 14.3	the textbook.	which follows after this errata list.
	110010111113		Error confirmed. Change "his" to
			"hits" in reprint.
1.4	D 11 1412	TYPO in the textbook: "his the	птертите.
14	Problem 14.13	ground." should be "hits the ground."	
			Error confirmed. Last line should
		In the ISM incorrect answer: v_D =	end with 17.7 m/s, as in final ISM
14	Problem 14.33	17.7 m/s (not 7.7 m/s)	MS.
			Intent should be clearer. In reprint,
			change the last part to read
			"determine the maximum
			compression imparted to the
			spring by the initial impact. Take e
			= 0.8 between the box and the
			plate. Assume that the plate slides
		Given the initial data (and even data	smoothly and reaches full
		within rather wide range) the block	compression before any secondary
		can strike the plate again, even	impact with the box."
		several times. And it is too hard to	
		calculate wether it happens. So, I've	Do not change ISM or end-of-
		changed the data the next way: the	book answer. If the tutorial is
		box weighs less then the plate now.	supposed to mirror the text, then
		So it changes the direction of its	make the above change in the
		velocity, and there will no multiple	tutorial as well, rather than making
1.5	Problem 15.82	collisions.	the box weigh less than the plate.
15			

			There is an error, but it is not with the labeling G_1 and G_2. The intent of the figure is to show a shift in the girl's center of gravity between the first position and the middle one. So the black dot in the first position (on the right) should be higher up the rope, let's say just above the girl's hand, and there should be a black dot at the
		The picture in the textbook is	junction of the three ropes in the middle position, just the same as
		incorrect. There is two G_2 points.	the black dot in the last position
15	Problem 15.108	The figure was changed with G_0.	(on the left).
		Typo in the ISM: question is asking to find force, however ISM mark 2	Error confirmed. Remove the first of the threee "Ans." labels.
		answers – Force and Moment. Also	Correct the matrix display to
4	Problem 4.55	there are display of matrix issue.	match final ISM MS.
		1 3	Not sure what they mean. If the
			issue is that the angle show in the
			the text is not actually 26 degrees
5	Problem 5.18	incompationals on the nicture	(not to scale), that is not a big deal and doesn't require a correction.
3	71001cm 3.16	incorrect angle on the picture	Not sure what this means. If the
			issue is that the angle show in the
			text is not actually 18 degrees (not
			to scale), that is not a big deal and
5	Problem 5.44	incorrect angle on the picture	doesn't require a correction.
			Not sure what this means. But I do
			see some errors. In the ISM, in the solution section on joint <i>D</i> , change
			subscript DB to subscript DE ,
			twice. And in the last line of the
			solution, change 0.577 P (T) to
		An error in ISM. The answer, which	0.289 P(T). Make corresponding
	D 11 (22	is not requested in the problem was	changes to the end-of-book
6	Problem 6.23	tagged with "ans" note.	answer.
			In the ISM, make the following changes: (1) add an additional
			term of - 1500 to the calculation
		An error in the calculations in ISM	for F_CH, per the MS; (2) Delete
		was found: the value CH is calculated	the "Ans." tag after the value for
		incorrectly. In addition, it is not	F_CH; (3) Restore part of the MS
		required to estimate it according to	material that was hand-deleted by
6	Problem 6.28	the task. It seems to be a misprint, and there should be CJ.	author, beginning with "Method of joints" and ending with the answer
6	F1001c111 0.28	mere should be CJ.	Joints and ending with the answer

			for F_CJ.
6	Problem 6.30	An error in ISM. The answer, which is not requested in the problem was tagged with "ans" note.	Delete the first "Ans." tag in the ISM solution.
6	Problem 6.34	An error in ISM. The answer, which is not requested in the problem was tagged with "ans" note: the force implemented to GJ is just an intermediate value.	Delete the first "Ans." tag in the ISM solution. (The end-of-book answer does not need to show F_GJ, but it does no harm and therefore no change is needed.)
6	Problem 6.67	Inconsistency between ISM and textbook. Question wording is different in ISM and Textbook.	Error confirmed. Change problem wording in ISM to match main text.
1R	Review Problem R1.2	There is an error in a_A for part B in ISM	In the ISM, in the first equation for part b), block A, change 20(0.3) to 50 - (20)(0.3).
1R	Review Problem R1.3	There is a typo in the textbook - x is missing in F: F = {10i+6yj+2zk}	I don't see any error. The x-component of the force is given as constant at 10, and that is how the solution treats it.
9	Problem 9.111	There is misprint in the ISM. Should be (5+h/5)	I am not sure what is being referred to. In the solution 9.111 that I am looking at, at the start A = theta z-bar r-wigglybar L should read A = theta SIGMA r-wigglybar L. However, the expression (10 + h/5) in the long middle equation is correct and should not change to 5 + h/5.
20	Problem 20.52	There is a wrong answer for a_B (I and j-components)	These problems are tricky, but on a quick review using a sketch and calculator, I see nothing amiss. Please state what values you think the components should have.
			Error confirmed. At one point there was confusion over what problem would appear as 19.32, and apparently we ended up duplicating the solution for 19.35 as the solution for 19.32. Need to trace back the pickup source for this problem and then pick up the correct solution. UPDATE: THE CORRECT SOLUTION AND ANSWER ARE PROVIDED
19	Problem 19.32	There is wrong solution in ISM.	BELOW.

19	Problem 19.34	wrong answer in ISM (I_A equals m*I^2/3) but when we use correct formula the answer has no physical sence	I see no error. We are not concerned with angular momentum about the fixed horizontal bar (although that, too, is conserved) but rather with angular momentum about the gymnast's own center of mass.
14	Problem 14.22	The solution and answer assume spring constants in lb/ft but the art shows them	Art in problem should be changed to show units of the spring constants as lb/ft rather than lb/in. This carries over into the problem art as it appears in the ISM.

Exercise 12-154:

For the ISM:

(1) Just before the section called "Acceleration" add a section on velocity:

Velocity: When t = 0.25 s, the vertical component of velocity is $8 \sin(40^\circ) - 9.81(0.25) = 2.690$ m/s. Then

$$v = \sqrt{6.128^2 + 2.690^2} = 6.692 = 6.69 \text{ m/s}$$
 Ans.
 $\theta = \tan^{-1}(2.690/6.128) = 23.697^\circ = 23.7^\circ$ Ans.

(2) In the section on Acceleration, right after "...23.70° with the x axis" add a parenthetic note before the concluding period:

(which confirms the velocity angle found above).

For back-of-book answer 12-154:

Right below the equation that begins with "y =", add the following:

$$v = 6.69 \text{ m/s}$$

$$\theta = 23.7^{\circ}$$

Exercise 14-3:

For the ISM:

SOLUTION

Equations of Motion: Since the crate slides, the friction force developed between the crate and its contact surface is $F_f = \mu_k N = 0.2N$. Applying Eq. 13–7, we have

$$+\uparrow \Sigma F_y = ma_y;$$
 $N + 1000 \left(\frac{3}{5}\right) - 800 \sin 30^\circ - 100(9.81) = 100(0)$ $N = 1321 \text{ N}$

Principle of Work and Energy: The horizontal components of force 800 N and 1000 N which act in the direction of displacement do positive work, whereas the friction force $F_f = 0.2(1321) = 264.2$ N does negative work since it acts in the opposite direction to that of displacement. The normal reaction N, the vertical component of 800 N and 1000 N force and the weight of the crate do not displace, hence they do no work. Since the crate is originally at rest, $T_1 = 0$. Applying Eq. 14–7, we have

$$T_1 + \sum U_{1-2} = T_2$$

$$0 + 800 \cos 30^{\circ}(s) + 1000 \left(\frac{4}{5}\right)s - \frac{264.2s}{2} = \frac{1}{2}(100)(6^2)$$

$$s = 3.54 \,\text{m}$$
Ans.

For back-of-book answer 14-3:

Change 1.35 m to 3.54 m.

Full Download: https://testbanklive.com/download/engineering-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-13th-edition-hibbeler-solutions-mechanics-statics-and-dynamics-and-dynamics-statics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-and-dynamics-

Exercise 19-32: Correct solution is pictured below. End-of-book answer is boxed in green.

The space satellite has a mass of 125 kg and a moment of inertia $I_z = 0.940 \text{ kg} \cdot \text{m}^2$, excluding the four solar panels A, B, C, and D. Each solar panel has a mass of 20 kg and can be approximated as a thin plate. If the satellite is originally spinning about the z axis at a constant rate $\omega_z = 0.5 \text{ rad/s}$ when $\theta = 90^\circ$, determine the rate of spin if all the panels are raised and reach the upward position, $\theta = 0^\circ$, at the same instant.

Mass Moment of Inertia: The mass moment inertia of the satelite about the cass when its solar panels are in lowered (flat) position is

$$(I_z)_1 = 0.940 + 4 \left[\frac{1}{12} (20) (0.2^2 + 0.75^2) + 20 (0.575^2) \right]$$

= 31.4067 kg·m²

The mass moment inertia of the satelite about z axis when its solar panels are in applied position is

$$(I_z)_1 = 0.940 + 4\left[\frac{1}{12}(20)(0.2^2) + 20(0.2^2)\right] = 4.4067 \text{ kg} \cdot \text{m}^2$$

Conservation of Angular Momentum: Applying Eq. 19-17, we have

$$(H_z)_1 = (H_z)_2$$

 $31.4067(0.5) = 4.4067(\omega_c)_2$
 $(\omega_c)_2 = 3.56 \text{ rad/s}$ Ans

